



FLAMESAFE® FS 900+ SEALANT

Elastomeric firestop

Product Features

- Underwriters Laboratories classified
- Factory Mutual approved
- Firestop systems listed for through-penetration and joint systems
- Listed in systems with up to 4 hour fire rating
- Tested to UL 1479 (ASTM E814), UL 2079 (ASTM E1966 and E1399), UL 723 (ASTM E84)
- Sound transmission tested in accordance with ASTM E90 Sound Transmission Class (STC) Rating 62
- ASTM G21-Testing for mold and mildew growth resistance. Tested by a third party independent laboratory to the ASTM G21-13 standard with Fungal Growth Rating results of zero.
- Water-based, easy to use and clean up
- Excellent adhesion to a variety of substrates and penetrants
- No solvents, silicones or outgassing
- Elastomeric
- Easy to apply
- Minimum 2 year shelf life

Description

FlameSafe® FS 900+ Sealant is cost-effective, water-based and cures to form a flexible shield against the spread of fire and smoke. It is available in grade : caulkable/trowe-
lable (CG)

FS 900+ does not contain solvents and, as a result, is not toxic and will not damage plastic pipes or cable jackets.

FS 900+ can be used in various penetrations and construction/architectural joint configurations. Examples of listed systems include metallic and non-metallic pipes, cable and HVAC penetrations, concrete floor-to-floor, floor-to-wall and wall-to-wall applications, as well as for concrete, CMU and gypsum head of wall applications requiring dynamic joint movement. FS 900+ is a versatile, yet economical solution for a wide range of through-penetration and joint construction conditions.



FlameSafe FS 900+ Sealant

Physical Properties

Color	Red or gray
Weight	10.75 lbs/gal (1.3 kg/L)
Storage and installation temperatures	40° F to 120° F (4° C to 49° C)
Flame spread (UL 723/ASTM E84)	0
Smoke developed (UL 723/ASTM E84)	0

Application Guide


Penetrations	
Metallic	X
Non-metallic	X
Cables	X
Cable trays	
Insulated	X
Misc. electrical	X
HVAC	X
Mixed	X
Joints	
Perimeter Barrier (Curtain Wall)	X

Applicable Standards

FlameSafe FS 900+ is listed by Underwriters Laboratories Inc. and by Underwriters' Laboratories of Canada for 1, 2, 3 and 4 hour rated systems, in accordance with ASTM E814 (UL 1479/CAN 4-2115M), *Fire Tests of Through-Penetration Firestops* and UL 2079, *Standard for Fire Tests of Joint Systems*. FS 900+ is Factory Mutual approved and approved by the City of New York (MEA 41-00-M, Vol. II).

Installation

All contact surfaces must be free of loose dirt, scale, oil or other foreign material. Installation of material may vary according to the size of the opening being protected and the type of penetrant. Installation temperature should be between 40°F to 120°F (4°C to 49°C). Material may be installed using a standard caulk gun or troweled into place using a mason's trowel or putty knife. The self-leveling grade can be poured into the opening, then troweled to a smooth finish. FlameSafe FS 900+ dries quickly and in such a way that it can be painted and finished like the surrounding wall or floor.



*Refer to UL designs for full system description.





Availability

FlameSafe FS 900+ Sealant is available through authorized RectorSeal distributors in the following quantities:			
Description	Part No.	Volume	Std. Pack
Caulk Tubes			
Caulk Tube 10.3 oz (305 mL)	66831 (Red)	19 in. ³ (312 cm ³)	12
Caulk Tube* 31 oz (0.92 L)	66833 (Red)	57 in. ³ (934 cm ³)	12
Sausage Pack 20.2 oz (0.62 L)	66832 (Red)	37 in. ³ (606 cm ³)	12
Poly Pails			
Caulkable/Trowelable 5 gal (19.0 L)	66835 (Red)	66855 (Gray)	1,155 in. ³ (18,942 cm ³)


* For use with powered caulk gun only.
Call RectorSeal for tool recommendation.

Maintenance

Applications using FlameSafe FS 900+ are maintenance free, however, installations should be inspected periodically for accidental damage and repaired as per the original approved design.

Warranty

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable. However, since the conditions of use and application are beyond our control, RectorSeal shall not be liable for any damage, direct or consequential, resulting from the use of this material or design. RectorSeal's only warranty shall be to replace any of its products found to be defective.



Technical Support

RectorSeal provides technical support for all of its products, including FlameSafe FS 900+ Sealant. Call toll free at 800-231-3345 for assistance in product selection and for detailed specifications and approvals. We provide engineering analysis for unique firestopping applications, including system design drawings suitable for submittals. Material Safety Data Sheets are also available. More information is available on our web site at <http://flamesafe.rectorseal.com>.

Product Estimating Guide for Through-Penetrations
 (Volume in cubic inches assuming 0.5 inch required depth)

PIPE	SIZE	Size of Round Opening (Inches)																			
		1	2	3	4	5	6.5	7	8	9	10	11	12	13	14	15	16	17	18	19	20
0.54	¼	0.3	1.5	3.4	6.2																
0.68	⅜	0.2	1.4	3.6	6.1																
0.84	½	0.1	1.3	3.3	6.0																
1.05	¾		1.1	3.1	5.8																
1.32	1		0.9	2.8	5.6	9.1															
1.66	1¼		0.5	2.5	5.2	8.7															
1.90	1½		0.2	2.1	4.9	8.4															
2.38	2			1.3	4.1	7.6	11.9														
2.88	2½			0.3	3.0	6.6	10.9														
3.50	3				1.5	5.0	9.3	14.4	20.3	27.0											
4.00	3½					3.5	7.9	13.0	18.8	25.5											
4.50	4					1.9	6.2	11.3	17.2	23.9	31.3	39.6	48.6								
5.56	5						2.0	7.1	13.0	19.7	27.1	35.6	44.4								
6.63	6							2.0	7.9	14.5	22.0	30.2	39.3	49.1	59.7	71.1					
8.63	8									2.6	10.0	18.3	27.3	37.1	47.7	59.1					
10.75	10											2.1	11.2	21.0	31.6	43.0	51.1	68.1	81.8		
12.75	12													2.5	13.1	24.5	36.7	49.6	63.4		
14.00	14															11.4	23.5	36.5	50.2	64.8	80.1
16.00	16																	12.9	26.7	41.2	56.5
18.00	18																			14.5	29.8



rectorseal.com

For technical assistance call toll free at 800-231-3345

FlameSafe is a registered trademarks of RectorSeal.

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.